

Installation Guide

Gates

As a result of our AliWood Pty Ltd constant product improvement program, product changes may occur. As such, AliWood Pty Ltd reserves the right to change product without prior written notification.

Introduction

This guide will show you how to manufacture & install an AliWood Gate.

IMPORTANT

Please read all the instructions prior to starting the installation of your Gate. Understanding the process correctly will be the difference between a good and great result

The recommendations detailed in this guide produced by AliWood Pty Ltd are formulated along the lines of good building practice. They are not intended to be an exhaustive statement of all the relevant data. Further, as the success of projects depend on factors outside the control of AliWood Pty Ltd (e.g. quality of workmanship, particular design, detail requirements, etc). Aliwood Pty Ltd accepts no responsibility for, or in connection with, the quality of the projects or their suitability when completed.

Tools Required:






Step 1 - Measure your actual gate opening

Measure your actual opening, from this measurement deduct 50mm for a post either side & a further 15mm each side for the hardware spacing's (hinges and lock set). This measurement (A) is the actual width of your gate.

Measure the desired height of your gate. Deduct 50mm from this to arrive at your actual height (B) of your gate.




Step 2 - Cutting your frame and slats to length

Your gate frame is manufactured from 5050SSS (SSS = Single Side Slat) section. This is a 50 x 50mm box. From measurement (A), deduct 100mm (for the frame vertical sections) to arrive at the desired length you should cut your horizontal slats.

Hint: Deduct another 3-5mm so the slats slip in easily!



Step 3 - Cutting your 50 x 50 SSS to correct length




Creating your gate frame:

Measurement A is the length to cut the top and bottom rail at.

Measurement B is the length to cute the sides at.

Step 4 - Mitering 50 x 50 SSS to 45 Degrees




All corners should be cut at a 45 degree angle.

Hint: Be sure to lay the SSS side facing inward to collect your slats




Step 5 - Inserting Corner Connectors

Slide the AliWood corner connectors into place, creating the frame





Step 6 - Inserting Corner Connectors




Clamp the gate.

Hint: The side facing you is now the inside of you gate when you hang it.








Slip all your slats into place inside the 5050SSS section

Hint: At this point the slats should remain loose.

Step 8 - Fixing the Frame

D




Slide the very top slat hard into the SSS section of the top rail

Slide the very bottom slat into the 5050SSS section of the bottom rail

Hint: This will help hold the corners square whilst they are screwed off.




Step 9 - Fixing the Frame



Screw off your frame with 2 AliWood Large screws either side of the corner

Step 10 - Fixing the Frame




Place the AliWood Corner Gusset into position. Set your first slat where it is desired and screw off the corner gusset either side of the mitre joint. Repeat this process in each corner.

Hint: The corner gussets are important to help your gate stay square for years to come.



Step 11 - Slat Spacing



Space out your slats accordingly and use a spacer to retain the desired gap whilst you screw off each slat.


Hint: 15mm is recommended as a good privacy spacing and you can use an offcut slat for the spacer

One AliWood screw is required in each end of each slat.




Step 12 - Gate Fabrication Complete

The gate is now complete. You can remove any AliWood Protective plastic from your gate. Hinges and locks and be fitted at this point.





Completed Projects





+61 3 5831 2574 +61 3 5831 2575 sales@aliwood.com.au www.aliwood.com.au 445-447 Goulburn Valley Hwy Shepparton VIC 3631 PO Box 6458 Shepparton VIC 3632

ABN 25 613 779 025